

Cold Storage Doors

AUTOMATIC SLIDING DOOR

# THERMACLEAN® A-SERIES

## Key Features

- Hygienic and Acid-Resistant Steel Panel
- Double Perimeter Sealing
- Durable Full Rubber Gasket
- Covered or Tubular Running Gears
- Custom Opening Aids and Closures

## Major Benefits

- **Reliable Performance:**  
Stainless or coated steel door leaf and combined fittings safely ensure freezer requirements ranging from 23°F to -49°F.
- **Thermal Efficiency:**  
Tight-fitting perimeter sealing and gasket eliminates thermal leakage while preventing door leaf from freezing.
- **Streamlined Functionality:**  
Running gears, variable envelope construction, and custom opening aids and closures deliver convenient operational efficiency.

# THERMACLEAN® A-SERIES

## General Specifications

Application	Chill Room
Temperature Range	23F to -49F
Door Leafs	Single-leaf
Leaf Thickness	3.25" PU foam-filled
Leaf Surface	Galvanized steel sheet, painted or laminated/stainless steel sheet
Surface Variants	<b>Stainless steel</b> Stainless steel (circular brush finish, matt brush finish, strip finish)  <b>Galvanized steel</b> Silver, blue, red, yellow, or white
Track	Stainless steel track
Max Size	9.5" W x 9.5" H

## Constructions Variants

Classical sliding rail cover



Pipe sliding rail



Double doors



## Technical Drawing

