

Cold Storage Doors VERTICAL LIFT DOOR

## THERMACLEAN®

### Key Features

- Stucco-Embossed Galvanized Steel Panels
- Foamed-In-Place Polyurethane Insulation
- Corrosion-Resistant Track Hardware
- Polyester-Reinforced Adjustable Gaskets
- Power or Manually Operated Capability

### Major Benefits

- **Reliable Performance:**  
Tight-sealing capability and strong construction is designed to safely handle applications of up to 100°F delta T.
- **Space Efficiency:**  
Vertical door positioning maximizes floor and wall space, compared to swinging and sliding alternatives.
- **Proven Durability:**  
Frictionless operation, extruded aluminum structure, and protective hardware and track coating ensure product longevity.

# THERMACLEAN®

## General Specifications


Standard Size	11' W x 14' H
Cold Resistance	-40 °F
High Temperature	100 °F
Door Operation	Manual or automatic
Hardware / Track	Corrosion-resistant
Insulation	Filled with 4" foamed-in-place non-CFC polyurethane insulation with a minimum R-value of 32 at 20F.
Warranty	5 years

## Metal Cladding

Stainless Steel



Stucco Embossed




Galvanized Steel\*



\*Colors options available

## Vision Panels



12" x 14" sealed glass

**Cooler Door:** 2 layer, 1" thick

**Freezer Door:** 3 layer, 1" thick with 120 V.A.C. heat film

## Technical Drawing

